

C 60 life Top

Coloured Hardcore Skirting for PVC, CV and Linoleum



Döllken Weimar's solidcore skirtings are unique in their production technology: co-extrusion. Certified high density pine wood fibre cores are encased in a hard-wearing polyolefin. Döllken solidcore skirtings are very environment-friendly and therefore certified e.g. by GREENGUARD Certification. Very practical and timesaving; all solidcore skirtings can be installed with our system tools.


Key benefits of the C 60 life TOP/ C 100 life:

- **Flexible lip seals to the flooring**
- **High flexibility of the skirting**
- **Mitre tool for notching seamless external corners and ensuring the perfect fit of internal corners**



C 60 life Top / C 100 life

Coloured Hardcore Skirting for PVC, CV and Linoleum



TCF
totally
chlorinefree

C 60: 1 sales unit = 40 x 2.575 m

C 100: 1 sales unit = 20 x 2.575 m

Specification

- HDF core encased in chlorine-free hard-wearing polyblend based on PP/TPE
- for gluing in infills of floor covering

Accessories

1 sales unit = 10 pieces,
available in 6 colours:



End caps left/right (only for C 60)

Colours: white, light beige, grey, black, aluminium metallic, chocolate brown

Tools

- Mitre Tool Type 1001
- Measuring Template for easy, precise positioning of the Mitre Tool
- Edge Cutter (Skirting Scissors)

Installation recommendation



Döllken
Notch



Döllken
Hot-melt



Adhesive Tape
UZIN (only C 60)

The chosen fastening system depends on the soundness of the wall structure, which should be checked for appropriate quality and rigidity by the fitter. The skirting should be installed tension free. Positive tolerances are to be avoided. We recommend switchTec Toptac 35 contact film adhesive, which is perfect for use on the skirting. PVC and CV flooring can be glued in with switchTec Contact 40. Refer to the manufacturer's instructions for rubber and linoleum. Cut the flooring into strips 51 mm broad (C60) or 90 mm (VC 100) and affix them into the skirting. Refer to Döllken installation and maintenance instructions.

Colours C 60 life TOP

